

Overview

UPtyma 18.5 1U Rackmount Console Kit

The UPtyma 18.5 1U Rackmount console kit is a high performance KVM console that combines a HD 18.5” LCD monitor with keyboard and touch pad in a dense 1U form factor. The 1U rackmount form factor is designed to allow a KVM console switch to be mounted directly behind it. The HD display supports video resolutions from 640 x 480 through 1680 x 1050 at 60 and 75 Hz refresh rates.



UPtyma 18.5 1U Rackmount Console Kit Models

18.5 1U RM CONSOLE – TAA	AB200A
18.5 1U RM CONSOLE – UK	AB201A
18.5 1U RM CONSOLE – DE	AB202A
18.5 1U RM CONSOLE – FR	AB203A
18.5 1U RM CONSOLE – IT	AB204A

18.5 1U RM CONSOLE – ES	AB205A
18.5 1U RM CONSOLE – DK	AB206A
18.5 1U RM CONSOLE – NO	AB207A
18.5 1U RM CONSOLE – SE/FI	AB208A
18.5 1U RM CONSOLE – CH	AB209A
18.5 1U RM CONSOLE – PT	AB210A
18.5 1U RM CONSOLE – BE	AB211A
18.5 1U RM CONSOLE – RU	AB212A
18.5 1U RM CONSOLE – JPN	AB213A
18.5 1U RM CONSOLE – INTL	AB214A
18.5 1U RM CONSOLE – LA/ES	AB215A
18.5 1U RM CONSOLE – CA	AB216A
18.5 1U RM CONSOLE – NL	AB217A
18.5 1U RM CONSOLE – US	AB218A
18.5 1U RM CONSOLE – KR	AB219A
18.5 1U RM CONSOLE – CN	AB220A

Standard Features

Screen Size	18.5 - Inch
Screen Type	TFT LCD Flat Panel
Maximum resolution	1680 X 1050
Supported Refresh Rates	60 and 75
Pointing Device	3-Button Capacitive Touchpad and Scroll Bar
Keyboard	Low profile keyboard with integrated number pad
Connectivity	USB Keyboard, 2 USB pass-through, VGA, DisplayPort and RS232
Rack Space	1U
KVM in same U space	Yes
Rails & Slides	Tool-less installation
OSD Language Support	English, French, German, Japanese, Simple Chinese and Spanish
Operating System Support	Windows Server, RH Linux, SLES Linux
Warranty	1-year limited warranty

Technical Specifications

Physical Dimensions	H x W x D	1.66x17.17x17.05inches
		4.23x43.61x43.3cm
	Weight	11.43 lbs (5.2Kg)
Shipping Dimensions	Package (L x W x D)	22.9 x 7.9 x 24.5 inches
		58.1 x 20 x 61.3 cm
	Weight	25.3 lbs (11.45 kg)
Display	Type	TFT
	Display	LCD with Backlight
	Viewable (diagonal)	H = 178° V = 178°
	Maximum Resolution	1680 x 1050
	Response Time	TR = 14ms TF = 11ms
	Brightness	300cd/m ²
	Contrast Ratio	700 : 1
Supported Graphics	HD	640 x 480 through 1680 x 1050
	Refresh rates	60 and 75 Hz
Power Source	AC Adapter	90 to 264 VAC 47 to 63Hz 36W
	Maximum Power	<36W
Keyboard Keys	101,102 or 106 layout (Depending on Country)	also includes inverted T scroll keys and Windows keys
	Keyboard/Touchpad Output	USB 2.0

Environmental Temperature	Operating	0° C to 50°C
	Storage	-20°C to +60°C
Humidity	Operating	20% RH to 90% RH
	Storage	10% RH to 90% RH
Altitude	Operating	3048 meters max
	Storage	9144 meters max